

# 06OPzS0625 SOLAR

## (2V 625Ah @ 120hr)



**N** Part of our Network Power range

### Performance characteristics


Nominal Voltage	2V
Number of cells	1
Design Life	20 years
<b>Nominal Capacity 20°C (68°F)</b>	
120 hour rate (5.2A, 1.85V)	625Ah
48 hour rate (11.3A, 1.80V)	543Ah
10 hour rate (48A, 1.8V)	480Ah
<b>Internal Resistance</b>	
Fully Charged Battery 20°C (68°F)	0.57mOhm
<b>Electrolyte</b>	
Nominal S.G at 20°C = 1.240kg/l	
<b>Operating Temperature Range</b>	-20-55°C
<b>Maximum Discharge Current 20°C (68°F)</b>	625A
<b>Charge Methods: Constant Voltage Charge 20°C (68°F)</b>	
Cycle use	2.40V (time limited)
Maximum charging current	192A
Standby use	2.25V ± 1%
Temperature compensation	-3.0mV/°C/Cell
<b>Terminal Torque</b>	23Nm

### Capacities C10-C240

Cell Type Ue (100%) / VPC	C10	C12	C20	C24	C48	C72	C100	C120	C240
Ref Temp	20°C	20°C	20°C	20°C	20°C	20°C	20°C	20°C	20°C

06OPzS0625 SOLAR	480	488	527	541	543	580	605	625	649
------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----

### Cycles vs DOD of OPzS Solar Power



### Features

- High energy density

---

- Robust tubular positive electrode design, compliant with DIN 40736

---

- Minimal maintenance due to low antimony alloy and large electrolyte volume

---

- Operating temperature -20°C to +55°C

---

- Low self discharge rate of approximately 3% per month at 20°C

---

- EUROBAT design life: Long Life >12 years

---

- Fully recyclable with low CO<sub>2</sub> footprint

---

- High cyclic performance

### Applications

- Solar/Wind Power Stations

---

- Traffic Systems

---

- Hydro Power Generation

---

- Off Grid Solutions

---


- Telecommunications/ Mobile Phone Stations

---

- Power Distribution Companies

### Dimensions and weight

Length	147 mm
Width	208 mm
Height (H1)	483.5 mm
Total height (H2)	509 mm
Dry weight	23.4 kg
Filled weight	32.2 kg



Compliant with IEC 60896-11 / IEC61427