

Modelos		PFS-MK90-12V100A h-P100	PFS-MK90-12V120A h-C32	PFS-MK90-25V60A h-C32	PFS-MK100-12V100Ah-P100	PFS-MK100-12V135Ah-C32	PFS-MK100-12V140A h-C40	PFS-MK100-25V75A h-C32	PFS-MK100-25V80Ah-C40	PFS-MK100-25V90Ah-C32T
Referencia		1010715	1010716	1010631	1007503	1010717	1010718	1009305	1010719	1010720
Capacidad		100 Ah	120 Ah	60 Ah	100 Ah	135 Ah	140 Ah	75 Ah	80 Ah	90 Ah
Energia		1280 Wh	1536 Wh	1536 Wh	1280 Wh	1728 Wh	1792 Wh	1920 Wh	2048 Wh	2304 Wh
Tensión nominal		12,8 V		25,6 V	12,8 V			25,6 V		
Rango de tensión		10 - 14,4 V		20 - 28,8 V	10 - 14,4 V			20 - 28,8 V		
BMS		100 A	120 A	60 A	SMART 100 A					
Corriente de carga nominal		25 A	30 A	15 A	25 A	34 A	35 A	19 A	20 A	23 A
Corriente de carga máxima		50 A	60 A	30 A	50 A	68 A	70 A	38 A	40 A	45 A
Corriente de descarga nominal		50 A	60 A	30 A	50 A	68 A	70 A	38 A	40 A	45 A
Corriente de descarga máxima		100 A	120 A	60 A	100 A	135 A	140 A	75 A	80 A	90 A
Tempe- ratura	Carga	0 - 55 °C	0 - 60 °C		0 - 55 °C	0 - 60 °C	0 - 55 °C	0 - 60 °C	0 - 55 °C	0 - 60 °C
	Descarga	-20 - 60 °C	-30 - 60 °C		-20 - 60 °C	-30 - 60 °C				
	Almacenamiento	-10 - 35 °C	-10 - 25 °C		-10 - 35 °C	-10 - 25 °C				
Tipo celda		Cilindrica			Prismática	Cilindrica				
Caja		MODELO 12-90			MODELO 12-100					
Dimensiones		306 x 172 x 215 mm			330 x 172 x 220 mm					
Material caja		ABS			ABS					
Terminales caja		M8			M8					
Garantia		2 años			2 años					