

Modelos		PFS-MK150-12V180Ah-C32	PFS-MK150-12V200Ah-C40	PFS-MK150-12V200Ah-P100	PFS-MK150-25V60Ah-C32	PFS-MK150-25V80Ah-C40	PFS-MK150-25V100Ah-P100
Referencia		1007505	1010725	1010726	1010727	1010728	1010729
Capacidad		180 Ah	200 Ah	200 Ah	60 Ah	80 Ah	100 Ah
Energía		2304 Wh	2560 Wh	2560 Wh	1536 Wh	2048 Wh	2560 Wh
Tensión nominal		12,8 V			25,6 V		
Rango de tensión		10 - 14,4 V			20 - 28,8 V		
BMS		SMART 100 A					
Corriente de carga nominal		45 A	50 A	50 A	15 A	20 A	25 A
Corriente de carga máxima		90 A	100 A	100 A	30 A	40 A	50 A
Corriente de descarga nominal		90 A	100 A	100 A	30 A	40 A	50 A
Corriente de descarga máxima		180 A	200 A	200 A	60 A	80 A	100 A
Temperatura	Carga	0 - 60 °C	0 - 55 °C		0 - 60 °C	0 - 55 °C	
	Descarga	-30 - 60 °C		-20 - 60 °C	-30 - 60 °C		-20 - 60 °C
	Almacenamiento	-10 - 25 °C		-10 - 35 °C	-10 - 25 °C		-10 - 35 °C
Tipo celda		Cilindrica		Prismática	Cilindrica		Prismática
Caja		MODELO 12-150					
Dimensiones		501 x 185 x 242 mm					
Material caja		ABS					
Terminales caja		M8					
Garantía		2 años					