

Modelos		PFS-MK22-12V30Ah-C32	PFS-MK22-12V40Ah-C40	PFS-MK22-25V15Ah-C32	PFS-MK22-25V20Ah-h-C40	PFS-MK35-12V40Ah-C40	PFS-MK35-12V45Ah-C32	PFS-MK35-25V15Ah-C32	PFS-MK35-25V20Ah-C40
Referencia		1010698	1010699	1010156	1010700	1010701	1010702	1010703	1010704
Capacidad		30 Ah	40 Ah	15 Ah	20 Ah	40 Ah	45 Ah	15 Ah	20 Ah
Energia		384 Wh	512 Wh	384 Wh	512 Wh	512 Wh	576 Wh	384 Wh	512 Wh
Tensión nominal		12,8 V		25,6 V		12,8 V		25,6 V	
Rango de tensión		10 - 14,4 V		20 - 28,8 V		10 - 14,4 V		20 - 28,8 V	
BMS		30 A				40 A		30 A	
Corriente de carga nominal		8 A	10 A	4 A	5 A	10 A	11 A	4 A	5 A
Corriente de carga máxima		15 A	20 A	8 A	10 A	20 A	23 A	8 A	10 A
Corriente de descarga nominal		15 A	20 A	8 A	10 A	20 A	23 A	8 A	10 A
Corriente de descarga máxima		30 A	40 A	15 A	20 A	40 A	45 A	15 A	20 A
Temperatura	Carga	0 - 60 °C	0 - 55 °C	0 - 60 °C	0 - 55 °C	0 - 55 °C	0 - 60 °C		0 - 55 °C
	Descarga	-30 - 60 °C				-30 - 60 °C			
	Almacenamiento	-10 - 25 °C				-10 - 25 °C			
Tipo celda		Cilindrica				Cilindrica			
Caja		MODELO 12-22				MODELO 12-35			
Dimensiones		174 x 165 x 122 mm				195 x 130 x 154 mm			
Material caja		ABS				ABS			
Terminales caja		M5				M6			
Garantia		2 años				2 años			