



Modelos		PFS-MK100-12V100Ah-P100	PFS-MK100-12V135Ah-C32	PFS-MK100-12V140Ah-C40	PFS-MK100-25V75Ah-C32	PFS-MK100-25V80Ah-C40	PFS-MK100-25V90Ah-C32T
Referencia		1007503	1010717	1010718	1009305	1010719	1010720
Capacidad		100 Ah	135 Ah	140 Ah	75 Ah	80 Ah	90 Ah
Energía		1280 Wh	1728 Wh	1792 Wh	1920 Wh	2048 Wh	2304 Wh
Tensión nominal		12,8 V			25,6 V		
Rango de tensión		10 - 14,4 V			20 - 28,8 V		
BMS		100 A					
Corriente de carga nominal		25 A	34 A	35 A	19 A	20 A	23 A
Corriente de carga máxima		50 A	68 A	70 A	38 A	40 A	45 A
Corriente de descarga nominal		50 A	68 A	70 A	38 A	40 A	45 A
Corriente de descarga máxima		100 A	135 A	140 A	75 A	80 A	90 A
Temperatura	Carga	10	10	30	10	30	10
	Descarga	0 - 55 °C			0 - 60 °C		
	Almacenamiento	-20 - 60 °C			-30 - 60 °C		
Tipo celda		Prismática	Cilíndrica				
Caja		12-100					
Dimensiones		330 x 172 x 220 mm					
Material caja		ABS					
Terminales caja		M8					
Peso		9984 g	12960 g	13944 g	14400 g	15936 g	17280 g
Garantía		2 años					