



Modelos		PFS-MK120-12V100Ah-P100	PFS-MK120-12V160Ah-C40	PFS-MK120-12V165Ah-C32	PFS-MK120-25V75Ah-C32	PFS-MK120-25V80Ah-C40
Referencia		1010721	1010722	1008306	1010723	1010724
Capacidad		100 Ah	160 Ah	165 Ah	75 Ah	80 Ah
Energía		1280 Wh	2048 Wh	2112 Wh	960 Wh	1024 Wh
Tensión nominal		12,8 V			25,6 V	
Rango de tensión		10 - 14,4 V			20 - 28,8 V	
BMS		100 A				
Corriente de carga nominal		25 A	40 A	41 A	19 A	20 A
Corriente de carga máxima		50 A	80 A	83 A	38 A	40 A
Corriente de descarga nominal		50 A	80 A	83 A	38 A	40 A
Corriente de descarga máxima		100 A	160 A	165 A	75 A	80 A
Temperatura	Carga	10		10		30
	Descarga	0 - 55 °C	0 - 55 °C	0 - 60 °C	0 - 60 °C	0 - 55 °C
	Almacenamiento	-20 - 60 °C	-30 - 60 °C			
Tipo celda		Prismática	Cilíndrica			
Caja		12-120				
Dimensiones		406 x 173 x 236 mm				
Material caja		ABS				
Terminales caja		M8				
Peso		9984 g	15936 g	15840 g	14400 g	15936 g
Garantía		2 años				