

Modelos		PFS-MK70-12V100Ah-P100	PFS-MK70-12V105Ah-C32	PFS-MK70-12V120Ah-C32T	PFS-MK70-12V120Ah-C40	PFS-MK70-25V60Ah-C40	PFS-MK70-25V60Ah-C32
Referencia		1010710	1010711	1009727	1010712	1010713	1010714
Capacidad		100 Ah	105 Ah	120 Ah	120 Ah	60 Ah	60 Ah
Energía		1280 Wh	1344 Wh	1536 Wh	1536 Wh	1536 Wh	1536 Wh
Tensión nominal		12,8 V				25,6 V	
Rango de tensión		10 - 14,4 V				20 - 28,8 V	
BMS		SMART 100 A					
Corriente de carga nominal		25 A	26 A	30 A	30 A	15 A	15 A
Corriente de carga máxima		50 A	53 A	60 A	60 A	30 A	30 A
Corriente de descarga nominal		50 A	53 A	60 A	60 A	30 A	30 A
Corriente de descarga máxima		100 A	105 A	120 A	120 A	60 A	60 A
Temperatura	Carga	0 - 55 °C	0 - 60 °C		0 - 55 °C		0 - 60 °C
	Descarga	-20 - 60 °C	-30 - 60 °C				
	Almacenamiento	-10 - 35 °C	-10 - 25 °C				
Tipo celda		Cilindrica					
Caja		MODELO 12-70					
Dimensiones		258 x 167 x 209 mm					
Material caja		ABS					
Terminales caja		M8					
Garantía		2 años					