## TECHNICAL DATA SHEET



Type no.		EFB PRO 575 11
Article no.		012575110101
EAN/GTIN no.		9005753098695
Application		Starter battery start-stop
Electrical data		
Rated voltage		12V
Rated capacity		75 Ah (K20)
Cold start current		700 A (EN)
Dimensions and weights		
Box Length max.	H6 278mm	X Carrier Manager
Width max.	175mm	BTARTISTOP
Box height max.	190mm	Banner
Total height max.	190mm	RUNNING BUIL EFB PROTensidenal  A BUIL BUIL PROTECTION
Battery weight	Ca. 19,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		64
Pallet ID		Euro pallet
Items per layer		16
Features		
Base hold-down		B13
Layout		0
Terminal		1
Separator		PE bag separator with glass nonwoven
Degassing		Battery with central degassing
Flame arrester		Integrated
Performance identification		W4 - C2 - V3 - M2 (E3)
Maintenance 1)		
Water consumption		W4
Refill water		Distilled or demineralised (DIN 43530)
Self-discharge		Approx. 3 % per month
Charging current		Approx. 1/10 of the rated capacity
Charging voltage 2)		max. 14,8 V

- $^{\mbox{\scriptsize 1}})$  All the listed values relate to room temperature +25° C
- <sup>2</sup>) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!
- 1 Document DBTBAT00339 prepared on 2021-04-19; Rights relating to changes and errors retained. original