



Type Designation	4020
Designation IEC	LR20
System	Zn-MnO <sub>2</sub> (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	17000 (50mA cont. / 0,8V cut-off)
Permissible Temperature Range	- 20 °C ... 60 °C
Weight, approx. [g]	140,4
Volume [ccm]	51.3

Dimensions [mm]

min: max:

Ø	32.3	34.2
A	-	61.5
B	59.5	-
C	18.0	-
E	-	1.0
F	-	9.5
G	1.5	-



Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage[V]	0.9
4M/15M,8H/D,7D/W	2.2 Ω	Time [h]	26,8
Portable lighting		Capacity [Ah]	13,9
		Energy [Wh]	16,0
Discharge Type	Load	End Voltage[V]	0.8
1H/D,7D/W	2.2 Ω	Time [h]	28,0
Toy		Capacity [Ah]	14,2
		Energy [Wh]	16,0
Discharge Type	Load	End Voltage[V]	0.9
2H/D,7D/W	600 mA	Time [h]	18,9
Portable Stereo		Capacity [Ah]	11,4
		Energy [Wh]	12,9

\* In consideration of typical loss of capacity at storage and application.