

## FLOODED DEEP CYCLE BATTERY

8 LC GC



Series	LC	Warranty	1 Year
Volts	8	BCI	GC2
Cells	4	Plates/Cell	11
Terminal Type	UTL		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18 x 1-1/2"		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)		
Float Voltage Range	2.25 V/cell @ 25°C (77°F)		
Self-Discharge Rate	5%-10% per month at 25°C (77°F)		

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	469		
Marine Crank Amps (MCA) 32°F / 0°C	586		
Reserve Capacity (RC @ 25A)	284 Minutes		
Reserve Capacity (RC @ 75A)	79 Minutes		

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 5 Hour Rate	119 Ah	23.8 A
@ 10 Hour Rate	132 Ah	13.2 A
@ 20 Hour Rate	150 Ah	7.5 A

Amphère hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

## Specifications




Weight	27 kg	59.5 lbs
Length	259 mm	10.19"
Width	181 mm	7.13"
Height Inc. Term.	279 mm	11"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	57 mm	2.25"
Container	Polypropylene	
Cover	Polypropylene	
Handles	Top Molded Strap Brackets	

## Cycle Life vs. Depth of Discharge



## Voltage vs. Depth of Discharge

