

SERIE TFS & RS

AGM CICLO PROFUNDO

Características

- Tecnología AGM.
- Diseño de vida extremadamente alto en uso cíclico.
- Clasificación EUROBAT: 12 + Larga Vida.
- Baterías VRLA, sin mantenimiento, 99% eficiencia en la recombinación interna de gases.
- Fácil instalación y comprobación.
- Carcasa de ABS V0, retardante de llama.
- Batería 100% reciclable.

Aplicaciones

Energía fotovoltaica, auto caravanas, caravanas, barcos, carretillas elevadoras, plataformas elevadoras, vehículos eléctricos, barredoras, fregadoras, elevadores, apiladores, luminarias de carretera.

DEEP CYCLE AGM

Main Features

- AGM technology.
- Extremely high cyclic life.
- EUROBAT classification; 12+ years design life, Long Life.
- VRLA batteries, maintenance free, internal gas recombination efficiency 99%.
- Easy installation and commissioning.
- ABS V0 (flame retardant) container and lid.
- Battery 100% recyclable.

Main uses

Solar energy systems, mobile homes, street solar lighting, vessels, fork lifts, lifting platforms, electrical vehicles, sweepers, scrubbing machines, electric stackers, etc.

Model	Nominal Voltage (V)	Rated Capacity (AH) 10HR	Dimension								Weight kg	I.R.	Terminal type
			Length		Width		Height		Total Height				
			mm	in.	mm	in.	mm	in.	mm	in.			
UP-TFS250-12	12	250	555	21.8	125	4.9	320	12.6	320	12.6	57.3	4.03	1+1 FA
UP-RS250-6	6	255	386	15.3	168	6.7	232	9.1	232	9.1	35.0	1.4	1+1 TA
UP-RS388-4	4	388	386	15.3	168	6.7	232	9.1	232	9.1	36.0	0.81	1+1 TA
UP-RS500-2	2	500	386	15.3	168	6.7	232	9.1	232	9.1	28.5	0.39	2+2 FA
UP-RS625-2	2	625	386	15.3	168	6.7	232	9.1	232	9.1	32.0	0.35	2+2 FA
UP-RS775-2	2	775	386	15.3	168	6.7	232	9.1	232	9.1	36.0	0.31	2+2 TA

* Las medidas y especificaciones están sujetas a modificaciones sin previo

* Technical specifications may be change without any notice,

